


## Geberit Mepla elbow adapter 90° with male thread



Example image



### Application purposes

- For chemicals and technical liquids
- For extinguishing water (wet/dry, dry)
- For extinguishing water (wet)
- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For compressed air (oil purity class 0–3)
- For negative pressure

- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

### Characteristics

- Leaky if unpressed
- O-ring made of EPDM
- Pressing nipple with transparent protective cap

### Technical data

Product material | Brass CW617N

Art. no.	DN	d, ø	R	arc	L	H	Z
611.252.00.5	12 / 15	16 mm	1/2 "	90 °	4.8 cm	3 cm	2.3 cm
612.252.00.5	15	20 mm	1/2 "	90 °	5.1 cm	3.2 cm	2.3 cm
612.253.00.5	15 / 20	20 mm	3/4 "	90 °	5.3 cm	3.4 cm	2.5 cm
613.253.00.5	20	26 mm	3/4 "	90 °	5.7 cm	4 cm	2.5 cm
613.254.00.5	20 / 25	26 mm	1 "	90 °	5.9 cm	4.3 cm	2.7 cm
614.254.00.5	25	32 mm	1 "	90 °	5.9 cm	4.6 cm	3.1 cm
615.255.00.5	32	40 mm	1 1/4 "	90 °	7 cm	5.3 cm	3.6 cm