


## Geberit Mepla bend adapter 90° with female thread



Example image



### Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For service water
- For rainwater with a pH value of > 6.0
- For seawater
- For extinguishing water (wet)
- For extinguishing water (wet/dry, dry)
- For chemicals and technical liquids

- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

### Characteristics

- Leaky if unpressed
- O-ring made of EPDM
- Pressing nipple with transparent protective cap

### Technical data

Product material | Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, ø	Rp	arc	L	L1	Z	Z1
601.256.00.5	12 / 15	16 mm	1/2 "	90 °	2.2 cm	5 cm	0.9 cm	2.4 cm
601.257.00.5	12 / 20	16 mm	3/4 "	90 °	3.5 cm	5 cm	2 cm	2.4 cm
602.256.00.5	15	20 mm	1/2 "	90 °	2.5 cm	5.3 cm	1.2 cm	2.5 cm
602.257.00.5	15 / 20	20 mm	3/4 "	90 °	3.5 cm	5.3 cm	2 cm	2.5 cm
603.257.00.5	20	26 mm	3/4 "	90 °	3 cm	6.1 cm	1.5 cm	2.9 cm
603.258.00.5	20 / 25	26 mm	1 "	90 °	3.4 cm	6.5 cm	1.5 cm	3.3 cm
604.258.00.5	25	32 mm	1 "	90 °	3.6 cm	6.2 cm	1.9 cm	3.4 cm
605.259.00.5	32	40 mm	1 1/4 "	90 °	4.3 cm	7.3 cm	2.2 cm	3.9 cm
606.256.00.5	40	50 mm	1 1/2 "	90 °	4.8 cm	8.1 cm	2.8 cm	4.3 cm
607.256.00.5	50	63 mm	2 "	90 °	5.7 cm	11.9 cm	3.1 cm	5.2 cm